









TECHNICAL SPECIFICATION

No 1

Dry-pressed ceramic tiles with a low water absorption rate $0.5\% < E \leq 3\%$ EN 14 411 Bl_b attachment H,
 Fasade tiles – UGL

TYPE	COLOUR	SURFACE
ELEVATION 245x65x6,5	ROT, BURGUND, COUNTRY WIŚNIA	FLAT, RUSTICO

	PROPERTIES	STANDARD	STANDARDS REQUIREMENTS	AVERAGE PERFORMANCE PARAMETERS
	WATER ABSORPTION [%]	PN-EN ISO 10545-3	$0,5 < E \leq 3,0$	$0,5 < E \leq 2,5$
	BREAKING STRENGTH [N/mm ²]	PN-EN ISO 10545-4	≥ 30	> 35
	BREAKING FORCE [N]	PN-EN ISO 10545-4	≥ 700	> 900
	FROST RESISTANCE	PN-EN ISO 10545-12	required	frost resistant
	RESISTANT TO HOUSEHOLD CHEMICALS AND SWIMMING POOL SALTS	PN-EN ISO 10545-13	min. UB	UA
	CHEMICAL RESISTANCE	PN-EN ISO 10545-13	declared	ULA, UHA
	RESISTANCE TO STAINING	PN-EN ISO 10545-14	declared	Class 5
	THERMAL SHOCK RESISTANCE	PN-EN ISO 10545-9	required	resistant

Technolog

 Opracował:  Barbara Szczepańska